

aquatreat[®]

Fine chemicals for water treatment

Industrial zone B 122 - Nieuwlandlaan 40/42
B-3200 Aarschot – BELGIUM
Tel. +32.16.56.21.21
E-mail: aquatreat@aquatreat.be
Website URL: <http://www.aquatreat.eu>

aquatreat[®] 205

Last revision : 10.10.2016

Data sheet

DESCRIPTION

- AQUATREAT 205 is a very efficient dispersant for organic material and it also stabilizes hardness-salts.
- AQUATREAT 205 contains sequestrants and a cationic polymer.
- AQUATREAT 205 will also improve decantation and filtration and it will separate oil from water.
- In cooling-water-systems, AQUATREAT 205 is injected continuously in the system.

PROPERTIES

Appearance	: yellow-brown liquid.
pH	: $5,6 \pm 1,0$
Density	: $1,09 \pm 0,02$
Solubility in water	: infinite

DOSAGE AND CONTROL

In open recirculating systems a dosage of 5 to 50 mg/l is used. For the filtration, AQUATREAT 205 is injected at a dosage of 2 to 20 mg/l. AQUATREAT 205 is injected as a concentrated solution but can also be injected as a diluted solution.

PACKAGING

Polyethylene drums of 22 or 220 litres, containers of 1000 litres.

HANDLING

AQUATREAT 205 is not harmful. Consequently no more than ordinary measures are to be taken while handling this product.