

## aquatreat® 550

Last revision: 03.08.2017

### Datasheet

---

#### DESCRIPTION

- AQUATREAT 550 is a broad spectrum liquid antiscalant for preventing fouling and scaling in reverse osmosis and nanofiltration systems.
- AQUATREAT 550 is a high concentrated blend of strong dispersants and sequestrants that will avoid, reduce and even remove deposits of inorganic and organic nature such as calcium carbonate, calcium sulphate, magnesium hydroxide, silicates, iron, mud and silt.
- AQUATREAT 550 can also be used in other systems where scaling and fouling problems can occur.

#### PROPERTIES

Appearance: light-green liquid

pH :  $6,4 \pm 0,2$

Density :  $1,11 \pm 0,02$

Solubility in water: infinite

#### DOSAGE AND CONTROL

Typical dosage rates are 2-20 mg/l on the feed water.

A method to determine its concentration in the treated water is available.

#### PACKAGING

Polyethylene drums of 22 or 220 litres or containers of 1000 litres.

#### HANDLING

Wear suitable protective clothing, gloves and eye-protection.

---

All the given information is correct to our current knowledge. None of the indications, compositions or applications have the intention of violating existing patents. Nothing may be duplicated and/or multiplied without our written consent.

---

