

aquatreat[®]

Fine chemicals for water treatment

Industrial zone B 122 - Nieuwlandlaan 40/42
B-3200 Aarschot – BELGIUM
Tel. +32.16.56.21.21
E-mail: aquatreat@aquatreat.be
Website URL: <http://www.aquatreat.eu>

aquatreat[®] 601

Last revision : 10.10.2016

Data sheet

DESCRIPTION

- AQUATREAT 601 is a liquid product, used to prevent corrosion and deposits in high pressure boilers.
- AQUATREAT 601 contains alkaline phosphates.
- AQUATREAT 601 is used to control the pH and the phosphate concentration.

PROPERTIES

Appearance	: colourless liquid
pH	: > 11
Density	: 1,05 ± 0,02
Solubility in water	: infinite

DOSAGE AND CONTROL

AQUATREAT 601 will be injected continuously into the feed tank or directly into the boiler (if a desuperheater is present). AQUATREAT 601 can be injected together with other treatment chemicals. AQUATREAT 601 will be dosed so that the concentration of phosphate in the boiler ranges between 5 and 10 ppm PO₄.

PACKAGING

Polyethylene drums of 22 or 220 litres or containers of 1000 litres.

HANDLING

AQUATREAT 601 is not toxic. The risks of manipulation are limited. In case of contact with skin or eyes, flush with plenty of water. Steam, produced by AQUATREAT 601 can be used in the food-production .