

aquatreat[®]

Fine chemicals for water treatment

Industrial zone B 122 - Nieuwlandlaan 40/42
B-3200 Aarschot – BELGIUM
Tel. +32.16.56.21.21
E-mail: aquatreat@aquatreat.be
Website URL: <http://www.aquatreat.eu>

aquatreat[®] 605

Last revision : 10.10.2016

Data sheet

DESCRIPTION

- AQUATREAT 605 is a liquid product, used to prevent corrosion and deposits in the boiler.
- AQUATREAT 605 contains polyphosphates, dispersants and an anti-foam.

PROPERTIES

Appearance	: light-yellow liquid
pH	: $4,3 \pm 1,0$
Density	: $1,23 \pm 0,02$
Solubility in water	: infinite

DOSAGE AND CONTROL

AQUATREAT 605 will be injected continuously in a concentrated or in a diluted form, in the feed-water-line or directly in the boiler. AQUATREAT 605 can be injected together with other treatment chemicals. AQUATREAT 605 will be dosed so that the concentration of phosphate in the boiler ranges between 40 and 80 ppm PO₄.

PACKAGING

Polyethylene drums of 22 or 220 litres or containers of 1000 litres.

HANDLING

AQUATREAT 605 is less toxic. The risks of manipulation are limited. In case of contact with skin or eyes, flush with plenty of water. Steam, produced by AQUATREAT 605 can be used in the food-production .