

# aquatreat<sup>®</sup>

*Fine chemicals for water treatment*

Industrial zone B 122 - Nieuwlandlaan 40/42  
B-3200 Aarschot – BELGIUM  
Tel. +32.16.56.21.21 E-  
mail: [aquatreat@aquatreat.be](mailto:aquatreat@aquatreat.be)  
Website URL: <http://www.aquatreat.eu>

## aquatreat<sup>®</sup> 690

Last revision : 10.10.2016

---

Data sheet

---

### DESCRIPTION

- AQUATREAT 690 is a liquid product, used to prevent corrosion and deposits in the boiler.
- AQUATREAT 690 protects the steam- and the condensate lines against corrosion. Also, the product will slowly remove existing deposits.
- AQUATREAT 690 contains dispersants, oxygen scavengers, alkali, volatile and neutralizing products and an anti-foam.
- AQUATREAT does not contain any phosphates.

### PROPERTIES

Appearance	: white-yellow liquid
pH	: $6,9 \pm 1,0$
Density	: $1,18 \pm 0,05$
Solubility in water	: infinite

### DOSAGE AND CONTROL

AQUATREAT 690 will be injected continuously in a concentrated or in a diluted form, in the feed-water-line or directly in the boiler. AQUATREAT 690 will be dosed so that the concentration of sulphite ranges between 30 and 60 ppm SO<sub>3</sub>, and a positive hydroxyle alkalinity is obtained in the boiler-water. The pH of the condensate must range between 7,5 and 8,5.

### PACKAGING

Polyethylene drums of 22 or 220 litres or containers of 1000 litres.

### HANDLING

AQUATREAT 690 is a reducing agent. Do not store with acids, alkali or oxidizing agents. Do not swallow. In case of contact with skin or eyes, flush with plenty of water. For eyes, get medical attention.