

# aquatreat<sup>®</sup>

*Fine chemicals for water treatment*

Industrial zone B 122 - Nieuwlandlaan 40/42  
B-3200 Aarschot – BELGIUM  
Tel. +32.16.56.21.21  
E-mail: [aquatreat@aquatreat.be](mailto:aquatreat@aquatreat.be)  
Website URL: <http://www.aquatreat.eu>

## aquatreat<sup>®</sup> 695

Last revision : 10.10.2016

---

Data sheet

---

### DESCRIPTION

- AQUATREAT 695 is a liquid product, used to prevent corrosion and deposits in the boiler.
- AQUATREAT 695 protects the steam- and the condensate lines against corrosion. Also, the product will slowly remove existing deposits.
- AQUATREAT 695 contains polyphosphates, dispersants, oxygen scavengers, alkali, volatile and neutralizing products and an anti-foam.
- AQUATREAT 695 is especially used in boilers with low pH- make-up water, like osmotic water or demi-water.

### PROPERTIES

Appearance	: white-yellow liquid
pH	: > 11
Density	: 1,17 ± 0,02
Solubility in water	: infinite

### DOSAGE AND CONTROL

AQUATREAT 695 will be injected continuously in a concentrated or in a diluted form, in the feed-water-line or directly in the boiler. AQUATREAT 695 will be dosed so that the concentration of sulphite ranges between 30 and 60 ppm SO<sub>3</sub>, and a positive hydroxyl alkalinity is obtained in the boiler-water. The pH of the condensate must range between 7,5 and 8,5.

### PACKAGING

Polyethylene drums of 22 or 220 litres, containers of 1000 litres.

### HANDLING

AQUATREAT 695 is a corrosive product.. Do not store with acids or oxidizing agents. Do not swallow. In case of contact with skin or eyes, flush with plenty of water.