

aquatreat®

Fine chemicals for water treatment

Industrial zone B 122 - Nieuwlandlaan 40/42
B-3200 Aarschot – BELGIUM
Tel. +32.16.56.21.21
E-mail: aquatreat@aquatreat.be
Website URL: <http://www.aquatreat.eu>

aquatreat® 698

Last revision : 10.10.2016

Data sheet

DESCRIPTION

- AQUATREAT 698 is a liquid product, used to prevent corrosion and deposits in the boiler.
- AQUATREAT 698 protects the steam- and the condensate lines against corrosion. Also, the product will slowly remove existing deposits.
- AQUATREAT 698 contains polyphosphates, dispersants, oxygen scavengers, alkali, volatile and neutralizing products and an anti-foam.
- AQUATREAT 698 is especially used in boilers with a very long condensate-line.

PROPERTIES

Appearance	: slightly yellow liquid
pH	: 10,8 +/- 1
Density	: 1,12 ± 0,02
Solubility in water	: infinite

DOSAGE AND CONTROL

AQUATREAT 698 will be injected continuously in a concentrated or in a diluted form, in the feed-water-line or directly in the boiler. AQUATREAT 698 will be dosed so that the concentration of sulphite ranges between 30 and 60 ppm SO₃, and a positive hydroxyl alkalinity is obtained in the boiler-water. The pH of the condensate must range between 7,5 and 8,5.

PACKAGING

Polyethylene drums of 22 or 220 litres, containers of 1000 litres.

HANDLING

AQUATREAT 698 is a slightly harmful product. Do not store with acids or oxidizing agents. Do not swallow. In case of contact with skin or eyes, flush with plenty of water.